MIRAI

experience the future

DML-520N100

20” / 51 cm LCD MONITOR

1400 x1050

TCO Development TCO'03 DISPLAYS www.tcodevelopment.com

DVI with

8 ms Ultra Fast

MIRAI
experience the future

DML-520N100
20” / 51 cm LCD MONITOR

Screen Size	408.24 (H) x 306.18 (V)
Driver Element	a-si TFT Active Matrix
Aspect Ratio	4 : 3
Pixel Pitch	0.2916 (H) x 0.2916 (V)mm
Panel Resolution	1400 x 1050
Pixel Arrangement	RGB Vertical Stripe
Tran Missive Mode	Normally White
Brightness	300 cd/m^2
Contrast Ratio (typ.)	500 : 1
Response Time (typ.)	8 ms (Tr:2 + Tf:6)
Viewing Angles (typ.)	150^0 (H) / 130^0 (V)
Display Color	16.2M
Horizontal Sync.	Positive / Negative
Vertical Sync.	Positive / Negative
Input Connector	D-Sub mini 15 pins, DVI-D 24 pins
Auto Adjust	Clock, Phase, H-Position, V-Position
Screen Scaling	VGA/SVGA/XGA/SXGA Full Screen Display
Power Management	VESA DPMS, DVI DMPM, Gost-R, ENERGY STAR® Compliance
COLOUR Adjustment	User, 6500K, 7500K, 9300K
Audio & Speaker	2.5W x 2
Tilt Angle	20^0(Upward) / -5^0(Downward)
Power Input	AC 100-240 V (Worldwide)
Input frequency	50/60Hz
Operation Mode	73W
Stand-by & Suspend Mode	<2W @230VAC 50Hz
Active-off Mode	<2W @230VAC 50Hz
Input System	RGB Seperate
Video Frequency Bandwidth	156 MHz dot clock
Dimension	463.6 (W) x 377.2 (H) x 192.4 (D) mm
Weight	4.5 Kg

Jupiterstraat 106, 2132 HE Hoofddorp, The Netherlands
TEL +31 (0)23 - 567 10 56 FAX +31 (0)23 - 567 10 67
info@nl-mirai.com

www.mirai.eu